



MBD


MANUAL BOTTOM DRIVE CARTON SEALER

The BestPack™ MBD Series is an operator-fed, adjustable carton sealer designed to efficiently fulfill light to heavy duty uniform top and bottom sealing carton closure application needs. The two bottom belts are powered by an 110V UL-approved electric motor. The MBD Series is also designed with four adjustable legs for quick and easy height modification to suit the needs of your production lines. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 30 CPM

Speed


N/A

Air Requirements

310 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(6.5" - 20.0")

Height (min. - max.)
(3.0" - 20.25")

Specifications based on MBD22-2

STANDARD FEATURES

- Two Bottom Belt Drive
- Telescopic Mast Design
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Adjustable Bed Height for:
MBD22-2 & MBD22-3 - 23.5" to 30.0"
- Upper Side Compression Unit
- Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Guide Rail Centering Mechanism
- Tape Roll Lengths: 1,000 yd., 1,500yd., 2,000yd.
- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Sealer Available in 2" or 3" Tape Heads
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm
- Electrical On/Off Box can be Mounted on Either Side of the Sealer

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Interlock Safety Gates
- Food Grade 304 Stainless Steel
- Infeed/Exit Conveyor w/ Unique L-Bracket Stabilizer

Contact us for more information

+1 (909) 670-8888 | sales@cbmsystem.com | www.cbmsystem.com

© 2024 CBM Systems, Inc. and BestPack Packaging Systems. All rights reserved.

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR MBD MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.***	SHIPPING WEIGHT (LBS)
MBD22-2 2" Tape Head	(42.0") x (28.8") x (70.3")	(6.0" - U) x (6.5" - 20.0") x (3.0" - 20.25")	(23.5" - 30.0")	Up to 20	310
MBD22-2H** 3" Tape Head	(42.0") x (28.8") x (70.3")	(6.0" - U) x (6.5" - 20.0") x (3.0" - 20.25")	(23.5" - 30.0")	Up to 30	310
MBD22-3 3" Tape Head	(42.0") x (28.8") x (70.3")	(6.0" - U) x (7.5" - 20.0") x (3.0" - 20.25")	(23.5" - 30.0")	Up to 20	310
MBD22-3H** 3" Tape Head	(42.0") x (28.8") x (70.3")	(6.0" - U) x (7.5" - 20.0") x (3.0" - 20.25")	(23.5" - 30.0")	Up to 30	310

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
** High Speed
*** Based on Customer Application



CBM Systems, Inc.
1599 Monte Vista Avenue
Claremont, CA 91711
sales@cbmsystem.com
(909) 670-8888

