

## B150-W

# BestPack™ Stretch Wrapper with Scale

Semi-automatic pallet wrapping machine

The BestPack™ B150-W combines our economic B150 model with a **digital built-in scale** to provide high performance and increased efficiency at a breakthrough price. This powerful scale has integrated load cells and allows for loads to be weighed as they're being wrapped. The BestPack™ B150-W sets itself apart from its competitors with its ease of use and adjustable control settings so every load is wrapped exactly to your standards.

CBM Systems BestPack™ Stretch Wrapper



## See what the BestPack™ B150-W can do for you!

1. Increase film utilization up to 50% for instant cost savings.
2. Shorten wrapping cycle time to as little as 1½ to 2 minutes.<sup>1</sup>
3. Adjustable film carriage and turntable speeds to improve load containment.



### Plug and play—Start wrapping right away

Affix film to your pallet—then press start. In many cases, operators won't even need to adjust wrap settings between loads.



### Improve load integrity and reduce shipping damage

Consistent performance and excellent load stability during transport keeps your load tightly secured more effectively than hand-wrapping.



### Boost productivity and save on time

The ability to weigh as you wrap improves your packaging process and ensures the utmost efficiency.

Contact us for more information


+1 (909) 670-8888 | [sales@cbmsystem.com](mailto:sales@cbmsystem.com) | [www.cbmsystem.com](http://www.cbmsystem.com)

© 2024 CBM Systems, Inc. and BestPack Packaging Systems. All rights reserved. 240112

## B150-W Specifications

Performance	
Speed*	25-35 loads/hour
Turntable Speed	12 RPM (variable)
Load Capacity	4,000 lbs
Turntable Size	58" diam
Max. Load Size	53" L x 53" W
Max. Load Height	82" H
Turntable	3/8" laser-cut steel plate
Weighing Types	Count & Accumulation
Weight Units	Lb/kg/g/oz/lb:oz
Indicator	Gross/Tare/Pre-set Tare/Zero
Film Delivery	
Film Delivery System	Motorized with Corner Compensating Dancing Bar
Film Stretch	Motorized Dual Rubber Rollers
Film Tension	Up to 220%
Motor-Assist Film Dispenser	Standard
Film Capacity	10" diam x 20"W (30"W option)
Film Carriage Speed	Adjustable
Height Sensor	Standard
Machine / Shipping Data	
Power Requirements	110V, 60 Hz, 20A
Pneumatic Requirements	None
Machine Dimensions	94" L x 59"W x 86" H
Weight (approximate)	1,000 lbs
Forklift Portable	Standard
Tilt-Down Tower	Standard

## Machine Footprint




**Make wrapping as easy as 1...  
2... 3...!**

*Set down your pallet, hit start, and get wrapping!*

- Detect your pallet load's height automatically.
- Reinforce the top and bottom of your load with extra wraps (combined setting 1-3).
- Pre-stretch film up to 150%.
- Low maintenance...heavy-duty frame and roller support system.

Specifications subject to change without notice.  
\* Wrap speeds may vary depending on load configuration.

## Options to improve performance



### Loading Ramp

Load your machine with a pallet jack using the made-to-fit loading ramp.



### Wrap Height Extension

Wrap tall loads with an extended wrap height column (16" increments) to accommodate your needs.



CBM Systems, Inc.  
1599 Monte Vista Avenue  
Claremont, CA 91711