

ROTARY ARM AUTOMATIC CONVEYORIZED


Heavy Duty Stretch Wrapping System


BestPack Rotary Arm Automatic Conveyorized Heavy Duty Stretch Wrapper with Four Structural Steel Legs Support. Built with Flexibility, Performance, Reliability and Integrity.




RAC-300

Machine Footprint:







Major Features

Controls

- PLC with 24V Control System
- ♦ Auto-Height Sensing Photoeye
- ◆ Current Overload Protection
- ◆ Separate Top and Bottom Wrap
- ♦ Variable Speed 15 RPM
- ♦ Adjustable Film Force to Load Control
- Touch Screen Operator Interface
- ◆ Electronic Soft Start/Stop
- Safety Fencing Monitoring

Rotary Arm & Film Delivery

- ♦ Standard 20" Film Rolls
- Motorized Pre-Stretch up to 300% other ratio available
- ◆ Lexan See Through Roller Cover
- Brush-On Film Tail Treatment
- Automatic Film Clamping and Cutting
- ◆ Pneumatic Brake for Quick Safety Stop
- Supported by Four Legs Design
- ◆ All Structural Steel Construction

Machine Specifications

Production Speed:	60 Loads / Hour Based on Load Configuration
Maximum Load Size:	48" L x 42" W x 80" H
Air Requirement:	3.6 CFM at 90 PSI
Power:	230 V, 15 AMP
Machine Dimension:	170" L x 162" W x 150" H

Information subject to change without notice. © 2016 CBM Systems Inc. All rights reserved.



©CBM SYSTEMS INC